


**DETAIL Y**

**MATERIALS:**

- HOUSING-PBT POLYESTER UL94V-0 MIXED GLASS FIBER. STANDARD COLOR-BLACK.
  - CONTACTS-0.35mm THICK PHOS-BRONZE PLATED WITH HARD GOLD AND GOLD FLASH IN SOLDER AREA.
  - SHIELD-0.25mm THICK COPPER ALLOY, PLATED WITH NICKEL.
- CAVITY CONFIRMS TO FCC RULES AND REGULATIONS PART 68,SUBPART F.



PC Board Layout Ref.

**Ordering Information**

AJT33L	8	8	1	X-0	X	4
Type	Positions	Contacts	Ports	Plating 3 = 30u" 4 = 50u"	Top & Side Tabs	

	LED1	LED2		LED1	LED2
1=	Yellow	Green	5=	Green	Red
2=	Green	Green	6=	Red	Green
3=	Green	Yellow	7=	Yellow	Yellow
4=	Green	Orange	8=	Grn/Ylw	Grn/Ylw

**\*Note:** AJT33L has replaced the AJT30L series. Pricing and specifications subject to change. Please review before ordering.

**Tolerance**  
unless otherwise specified

.0 ± .25  
.00 ± .13  
.000 ± .05



P/N: AJT33L881X-0X4 \*

Desc.: Side entry, shielded, LED, thru hole modular jack

Date: 7-27-09

Dimensions in mm Drawn By: Donna Mears