

G.SHDSL Magnetics



TM02304

- Designed to comply with the requirements of UL1950, BABT, CSA950, AS/N253260 and EN60950 to provide a supplementary insulation barrier with a working voltage of 250V
- Minimum interwinding breakdown voltage of 1500 Vrms
- Minimum interwinding breakdown voltage of 600 Vrms between pin 9 and 10 for 1 minute
- Operating and storage temperature range: -40° to +85° C
- Meets IEC 695, 2-2 flammability requirements
- PWB Process Capability: standard printed wiring board assembly techniques, total-immersion cleaning
- Reliability testing: shock, vibration, temperature cycling, temperature - humidity - bias

ELECTRICAL SPECIFICATIONS AT 25° C

Part Number	Turns Ratio ±2%	Inductance ¹ mH ±5%	Leakage Inductance ² µH max	DCR Ω max		Longitudinal Balance dB min	Insertion Loss dB max	Harmonic Distortion ³ dB max
	Chip : Line	Line Side	Chip Side	Chip Side	Line Side	10 kHz - 400 kHz	300 kHz	13.5 dBm @ 5 kHz
S560-6600-EZ	1 : 1.8	2.75	17	4.4	1.85	50	1.6	78

All measurements are made with pins 2 and 4 connected and pins 1 and 9 connected


1. Inductance measured at 10 kHz, 0.1 Vac

2. Measured at 100 kHz, 0.1 Vac

3. Measured with line impedance of 135 Ω and chip impedance of 41.66 Ω

SCHEMATIC


S560-6600-EZ




TM02304

MECHANICAL

S560-6600-EZ




SUGGESTED PAD LAYOUT



Dimensions are in inches [millimeters].

Standard dimension tolerance is ± 0.005 [0.13] unless otherwise noted.



USER FEED DIRECTION

ORIENTATION OF COMPONENT INSIDE POCKET

Tape and Reel Packaging

32 mm wide by 20 mm pitch; 13 inch OD, 4 inch ID
200 components per reel, maximum
Meets ANSI/EIA 481-2-A Carrier Tape Standards

©2006 Bel Fuse Inc. Specifications subject to change without notice. 04.06

CORPORATE

Bel Fuse Inc.
206 Van Vorst Street
Jersey City, NJ 07302
Tel 201-432-0463
Fax 201-432-9542
www.belfuse.com

FAR EAST

Bel Fuse Ltd.
8F / 8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706
www.belfuse.com

EUROPE

Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Suite G7, Preston
Lancashire, PR1 8UD, U.K.
Tel 44-1772-556601
Fax 44-1772-888366
www.belfuse.com