

# SD-D/SC/GY


Order No.: 2963815



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2963815>


Rail-mountable socket, housing color: gray, with screw connection, national version: Germany, housing width 45 mm



Commercial data	
GTIN (EAN)	 4 017918 606183
sales group	H070
Pack	5 pcs.
Customs tariff	85366990
Catalog page information	Page 602 (IF-2009)

**Product notes**

WEEE/RoHS-compliant since:  
07/14/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>General data</b>	
Nominal voltage $U_N$	250 V AC
Nominal current $I_N$	16 A AC
	10 A DC
Contact material	CuZn37

For country-specific use in	D
Color	gray
Insulating material	PA
Ambient temperature (operation)	-20 °C ... 60 °C
Ambient temperature (storage/transport)	-20 °C ... 60 °C
Standards/regulations	IEC 83
	DIN 49440-1
Width	45 mm
Height	75 mm
Depth	70.5 mm

**Connection data**

Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Type of connection	Screw connection
Stripping length	8 mm
Screw thread	M3

**Certificates / Approvals**


Certification

GOST, VDE-PZI

## Diagrams/Drawings

### Circuit diagram

---



**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;