



NO.	TITLE	DESCRIPTION
8	Over mold	PVC COLOR BLACK
7	INNER Mold	PE
6	FOIL	COPPER FOIL
5	TIN	TIN STICK, TIN WIRE
4	PCB	PCB
3	CONN P2	USB 2.0 BM, BLACK INSULATOR, CONTACT PLATING: Au 30u' SHELL PLATED NICKEL,(V/TIN PLATE)
2	CONN P1	USB C PLUG, BLACK INSULATOR,CONTACT PLATING : Pd-Ni 28u' + Gold 2u' SHELL PLATED NICKEL,(V/TIN PLATE)
1	CABLE	USB2.0 CABLE,BLACK PVC JACKET

P1		WIRING DIAGRAM				P2	
USB C PLUG		WIRE				USB 2.0 BM	
PIN	SIGNAL NAME	WIRE NUMBER	SIGNAL NAME	COLOR AVG	PIN	SIGNAL NAME	
A1,B1,A12,,B12	GND	1	GND_PWR+1	BLACK	4	GND	
A4,B4,A9,B9	VBUS	2	PWR_VBUS1	RED	1	VBUS	
A5	CC	N/A					
B5	vconn	N/A					
A6	Dp1	3	UTP_Dp	GREEN	3	D+	
A7	Dn1	4	UTP_Dn	WHITE	2	D-	
SHELL	SHIELD	BRIAD	SHIELD	BRIAD	SHELL	SHIELD	

Scale	FREE	Date		Name		Customer-No.	
<b>TOLERANCE</b>		Drawn	31.03.2015	Joanna	ASSMANN WSW-No.		
X.	±1	Approved	31.03.2015	Joanna	<b>A-USB31C-20B-XXX</b>		
.X	±0.5	Drawing-No.					
.XX	±0.25	ASSMANN					ASS 7349 CA
DIM	TOL	WSW components					rev00
		① Drawn	31.03.2015	Joanna	Drawing-No.		
		Replace					Sheet
Angle	TOL	Id.	Modification	Date	Name		

1

2

3

4

5

6

7

SV3725