

## Specification Sheet

Part Number: 181-11501



Solid Wall Wiring Duct, 1" X 1.5", Non-Adhesive, PVC, Gray, 120ft/Carton

<b>Article Number</b>	181-11501
<b>Type</b>	SD1X1.5
<b>Color</b>	Gray (GY)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Solid wall construction provides excellent coverage to keep wires clean.</li><li>• Durable material protects wires from damage, with long-lasting performance.</li><li>• A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.</li><li>• Available standard colors complement or contrast in light and dark environments.</li><li>• Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.</li><li>• Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement (Covers to be purchased separately.)</li></ul>
<b>Quantity Per</b>	carton

**Product Description**

HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire. Solid Wall wiring duct is designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6-foot lengths.

**Short Description**

Solid Wall Wiring Duct, 1" X 1.5", Non-Adhesive, PVC, Gray, 120ft/Carton

**Global Part Name**

SD1X1.5-PVC-GY

**Technical Description**

Non-Adhesive

**Length L (Imperial)**

6.0

**Length L (Metric)**

1.83

**Width W (Imperial)**

1.0

**Width W (Metric)**

25.4

**Height H (Imperial)**

1.57

**Height H (Metric)**

39.90

**Mounting Hole Centers (Imperial)**

4.0

**Material**

Polyvinylchloride (PVC)

**Material Shortcut**

PVC

**Flammability**

Self-Extinguishing

**Halogen free** No

**Operating Temperature (Metric)** +122°F (+50°C)

**Reach Complaint(Article 33)** No

**ROHS Complaint** Yes

**Certification/Specification WEB** EN 50085-2-3\_1A UL CSA EN 50085-1:2005 + A1:2013

**UL Recognized (US)** Yes

**Package Quantity(Imperial)** 120

**Package Quantity (Metric)** 36.58

**Customs Number** 3925900000