

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	18MAR2015	DW	CW
	B	ECR-15-018270	07DEC2015	DW	CW

T2111013101-000 SHOWN

NOTES:

1. TECHNICAL CHARACTERISTICS:  
 INSULATION MATERIAL: PC  
 RATED VOLTAGE: 1000V  
 RATED CURRENT: 200A  
 INSULATION RESISTANCE:  $\geq 400M\Omega$   
 RATED IMPULSE VOLTAGE: 8KV  
 POLLUTION DEGREE: 3  
 CONTACT RESISTANCE:  $\leq 0.5m\Omega$   
 FLAMMABILITY: UL94V-0  
 MATING CYCLES: 500 CYCLES  
 OPERATION TEMPERATURE:  $-40^{\circ}C \sim +125^{\circ}C$   
 WIRE RANGE:  $25mm^2 \sim 70mm^2$   
 CONTACT TYPE: CRIMP TYPE.

T2111013101-000 SHOWN  
带TE LOGO 和 UL MARK

注释:

1. 技术参数:  
 绝缘材料: PC  
 额定电压: 1000V  
 额定电流: 100A  
 绝缘电阻:  $\geq 400M\Omega$   
 脉冲电压: 8KV  
 污染等级: 3  
 接触电阻:  $\leq 0.5m\Omega$   
 阻燃等级: UL94V-0  
 插拔次数: 500次  
 工作温度:  $-40^{\circ}C \sim +125^{\circ}C$   
 接线范围:  $25mm^2 \sim 70mm^2$   
 接线类型: 压接

T2111013101-001 SHOWN, ALL DIMENSIONS ARE  
SAME AS T2111013101-000, EXCEPT WITHOUT LOGO  
不带 LOGO, 带UL MARK

T2111013101-001	HMN-001-MC WITHOUT LOGO
T2111013101-000	HMN-001-MC WITH LOGO
PART NUMBER	DESCRIPTION

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
	0 PLC $\pm$
	1 PLC $\pm$
	2 PLC $\pm$
	3 PLC $\pm$
	4 PLC $\pm$
	ANGLES $\pm$
MATERIAL	FINISH
-	-
-	-

DWN	18MAR2015	David Wang
CHK	18MAR2015	Chris Wang
APVD	18MAR2015	Xiang Xu
PRODUCT SPEC	108-137057	
APPLICATION SPEC	114-137057	
WEIGHT	-	
Customer Drawing		

		TE Connectivity	
		NAME HMN-001-MC	
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	©-T2111013101000	-
SCALE		SHEET	REV
1:1		1 OF 1	B

1470-19 (3/13)