

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	REVISED PER ECR-15-008877	17JUN2015	RS	JL
	B	REVISED PER ECR-15-011756	12AUG2015	RS	JL

NOTES:

1 MATERIAL:
 HOUSING: GF PBT, COLOR: BLACK
 CONTACTS: COPPER ALLOY, FINISH: Sn OVER Ni.

2 IP CODE

3 TE LOGO

4 N CODE

5 L CODE

6 PE CODE

7 RATED VOLTAGE

8 AREA FOR AGENCY APPROVAL LOGO

Technical drawings of a T-splitter connector. The drawings include:

- Front View (Left):** Shows the connector's face with three circular ports. Dimensions include a diameter of $\phi 13.3$ and a height of 24.0. Callouts 4, 5, and 6 are present.
- Side View (Middle):** Shows the profile of the connector. The total length is 61.1. Callouts 3, 5, and 7 are present. Dimensions 16.0 and 4.3 are shown at the bottom.
- Rear View (Center):** Shows the back of the connector with a rectangular cutout. Dimensions include a width of 16.3, a height of 44.7, and a diameter of $\phi 21.0$ (2X). Callouts 2, 3, 6, 7, and 8 are present. Text on the rear includes "IP67 400V" and the TE logo.
- Another Side View (Right):** Shows the connector from a different angle. Callouts 4, 6, and 7 are present.

3D VIEWS, FOR REFERENCE ONLY

Two 3D perspective views of the T-splitter connector, showing its cylindrical shape and the three ports on the front.

SCALE 1:1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C. DAILY 24FEB2014		
		CHK M. STOLLER 24FEB2014		
DIMENSIONS:		APVD	NAME	
mm		PRODUCT SPEC	T-SPLITTER, NECTOR M, 3 POSN, SEALED	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC	-	
0 PLC ±		114-32111	SIZE	CAGE CODE
1 PLC ±0.3		WEIGHT	A2	-
2 PLC ±0.20		Customer Drawing	DRAWING NO	RESTRICTED TO
3 PLC ±			G-2213434	-
4 PLC ±			SCALE	SHEET
ANGLES ±3°			5:2	1 OF 2
FINISH				REV
1				B

1471-9 (3/11)

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD		
-	-	SEE SHEET 1	-	-	-		

POLARIZATION KEYS

TYPE "A"	TYPE "B"	TYPE "C"
P/N 2213434-1	P/N 2213434-2	P/N 2213434-3

	T-SPLITTER CONNECTOR SEALED VERS. NECTOR M, 3 POSITION	C	2213434-3
	T-SPLITTER CONNECTOR SEALED VERS. NECTOR M, 3 POSITION	B	2213434-2
	T-SPLITTER CONNECTOR SEALED VERS. NECTOR M, 3 POSITION	A	2213434-1
NOTE	DESCRIPTION	POL. KEYS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C. DAILY 24FEB2014	TE Connectivity	
		CHK MOSTOLLER 24FEB2014		
DIMENSIONS: mm		APVD -	NAME T-SPLITTER, NECTOR M, 3 POSN, SEALED	
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ±0.3 2 PLC ±0.20 3 PLC ± 4 PLC ± ANGLES ±3° FINISH		PRODUCT SPEC 108-133014	RESTRICTED TO	
MATERIAL		APPLICATION SPEC 114-32111	SIZE A2	CAGE CODE -
		WEIGHT -	DRAWING NO C-2213434	SCALE 2:1
		Customer Drawing	SHEET 2 OF 2	REV B