



Die Datasheet, Logic Gate Device

Quad 2-Input NAND GATE

74AC00
74ACT00

Die Source:



27 mils x 31 mils x 14 mils

Backside : Silicon
Topside Metal: Aluminum



General Description:

The 74AC/ACT00 is a member of the Industries 74xxx series of Logic devices. The 74AC/ACT00 is a device description which contains (4) 2-Input NAND Gates.

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	CONDITIONS	LIMIT	UNITS
Supply Voltage	V_{CC}		-0.5 to +7.0	V
DC Input Diode Current	I_{IK}	$V_I = -0.5V$	-20.0	mA
		$V_I = V_{CC} + 0.5V$	20.0	mA
DC Input Voltage	V_I		-0.5 to $V_{CC} + 0.5$	V
DC Output Diode Current	I_{OK}	$V_O = -0.5V$	-20.0	mA
		$V_O = V_{CC} + 0.5V$	20.0	mA
DC Output Voltage	V_O		-0.5 to $V_{CC} + 0.5$	V
DC Output Source or Sink Current	I_O		± 50.0	mA
DC VCC Current	I_{CC}		± 50.0	mA
DC GND Current	I_{DD}		± 50.0	mA
Storage Temp	T_{STG}		-65.0 to +150	$^{\circ}C$
Max Junction Temp	T_J		150.0	$^{\circ}C$

IEEE / IEC LOGIC SYMBOL



RECOMMENDED OPERATING CONDITIONS

PARAMETER	TECH	SYMBOL	LIMIT	UNITS
Supply Voltage	AC	V_{CC}	2.0 to 6.0	V
	ACT		4.5 to 5.5	V
Input Voltage		V_I	0 to V_{CC}	V
Output Voltage		V_O	0 to V_{CC}	V
Operating Temperature		T_A	-40 to +85	$^{\circ}C$
Minimum Input Edge Rate	AC	$\Delta V / \Delta t$	125	mV/ns
	ACT		125	mV/ns

DC ELECTRICAL CHARACTERISTICS

PARAMETER	TECH	SYMBOL	VCC (V)	CONDITIONS	Guaranteed Limits		UNITS	NOTE	
					Min@25C	Min@85C			
Minimum HIGH level Input Voltage	AC	V_{IH}	3.0	$V_{OUT} = 0.1V \text{ or } V_{CC} - 0.1V$	2.10	2.10	V		
			4.5		3.15	3.15			
			5.5		3.85	3.85			
	ACT	V_{IH}	4.5		2.00	2.00			
			5.5		2.00	2.00			
Maximum LOW level Input Voltage	AC	V_{IL}	3.0	$V_{OUT} = 0.1V \text{ or } V_{CC} - 0.1V$	0.90	0.90	V		
			4.5		1.35	1.35			
			5.5		1.65	1.65			
	ACT	V_{IL}	4.5		0.80	0.80			
			5.5		0.80	0.80			
Minimum HIGH level Output Voltage	AC	V_{OH}	3.0	$I_{OUT} = -50\mu A$	2.90	2.90	V		
			4.5		4.40	4.40			
			5.5		5.40	5.40			
	AC	V_{OH}	3.0	$V_{IN} = V_{IL} \text{ or } V_{IH}, I_{OL} = -12mA$	2.56	2.46	V		
			4.5		3.86	3.76			
			5.5		4.86	4.76			
	ACT	V_{OH}	V_{OH}	$I_{OUT} = -50\mu A$	4.40	4.40	V		
					5.5	5.40			5.40
	ACT	V_{OH}	V_{OH}	$V_{IN} = V_{IL} \text{ or } V_{IH}, I_{OL} = -24mA$	3.86	3.76	V	1	
					5.5	4.86			4.76



Die Datasheet, Logic Gate Device

Quad 2-Input NAND GATE

74AC00
74ACT00

DC ELECTRICAL CHARACTERISTICS - CONT'D

PARAMETER	TECH	SYMBOL	VCC (V)	CONDITIONS	Guarenteed Limits		UNITS	NOTE
					Min@25C	Min@85C		
Maximum LOW level Output Voltage	AC	V _{OL}	3.0	I _{OUT} = -50uA	0.1	0.1	V	
			4.5		0.1	0.1		
			5.5		0.1	0.1		
	AC	V _{OL}	3.0	V _{IN} = V _{IL} or V _{IH} , I _{OL} = -12mA	0.36	0.44	V	
			4.5	V _{IN} = V _{IL} or V _{IH} , I _{OL} = -24mA	0.36	0.44		
			5.5	V _{IN} = V _{IL} or V _{IH} , I _{OL} = -24mA	0.36	0.44		
	ACT	V _{OL}	4.5	I _{OUT} = -50uA	0.1	0.1	V	
			5.5		0.1	0.1		
ACT	V _{OL}	4.5	V _{IN} = V _{IL} or V _{IH} , I _{OL} = -24mA	0.36	0.44	V		
		5.5	V _{IN} = V _{IL} or V _{IH} , I _{OL} = -24mA	0.36	0.44			
Maximum Input Leakage Current	AC	I _{IN}	5.5	V _I = V _{CC} or GND	±0.1	±1.0	uA	2
	ACT		5.5		±0.1	±1.0		
Minimum Dynamic Output Current	AC	I _{OLD}	5.5	V _{OLD} = 1.65V Max	--	75	mA	
	ACT		5.5		--	75		
	AC	I _{OHD}	5.5	V _{OHD} = 3.85V Min	--	-75	mA	
	ACT		5.5		--	-75		
Maximum Quiescent Supply Current	AC	I _{CC}	5.5	V _{IN} = V _{CC} or GND	2	20	uA	2
	ACT		5.5		2	20		

- Note(s):
1. All Outputs Loaded; thresholds on input associated with output under test
 2. I_{IN} and I_{CC} @ 3.0V are guaranteed to be less than or equal to the respective limit @ 5.5V VCC

AC ELECTRICAL CHARACTERISTICS

PARAMETER	TECH	SYMBOL	VCC (V)	CONDITIONS	Guarenteed Limits		Guarenteed Limits		UNITS
					Min@25C	Max@25C	Min@85C	Max@85C	
Propagation Delay	AC	t _{PLH}	5.0		1.5	9.0	1.0	9.5	ns
	ACT		5.0		1.5	9.0	1.0	9.5	
	AC	t _{PHL}	5.0		1.5	7.0	1.0	8.0	ns
	ACT		5.0		1.5	7.0	1.0	8.0	