

FO cable - FL FOC PN-C-HCS-GI-200/230 - 2313410

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



PROFINET HCS GI fiber cables, duplex 200/230 μm , increased bandwidth for Ethernet applications in particular. Robust PUR outer sheath. Heavy version suitable for drag chains and indoor installation, sold by the meter without plugs

Why buy this product

- Gradient index fiber for maximum performance requirements in terms of transmission bandwidth
- 2.2 mm individual wires made from polyvinyl chloride (PVC)
- Highly tear-resistant aramid strain relief elements
- Rugged polyurethane (PUR) outer sheath
- Rugged installation cable for indoor use
- PROFINET type C
- Halogen-free, ozone, and UV resistant
- Can be used in 10/100/1000 Mbps Ethernet systems



Key Commercial Data

Packing unit	1 STK
Custom tariff number	85447000
Country of origin	Germany

Technical data

Mechanical characteristics

Fiber	PCF gradient index, 200/230 μm
Cable diameter	8 mm
Duty cycle testing	Flexible cable conduit capable

Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
---------------------------------	------------------

FO cable - FL FOC PN-C-HCS-GI-200/230 - 2313410

Technical data

Ambient conditions

	-20 °C ... 70 °C (with quick mounting connector)
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Altitude	5000 m

Material data

Outer sheath, material	PUR
External sheath, color	green

Line characteristics

Cable type	HCS-GI
Cable abbreviation	J-V(ZN)12Y(ZN)11Y 2GK200/230 GI-HCS
Length of cable	Free input (1.0 ... 2000 m)
External cable diameter	8 mm
Wire colors	Black and orange with arrow labeling
External sheath, color	green
Outer sheath, material	PUR
Strain relief elements, external sheath	Non-metallic, aramide fiber
Cable weight	52 kg/km
Bending radius, single element	30 mm (Short-term) 30 mm (Permanent)
Bending radius, entire cable	65 mm (Short-term) 65 mm (Permanent)
Tensile strength short-term/long-term	2000 N / 600 N
Lateral pressure short term	400 N/cm
Lateral pressure, long-term	100 N/cm
Impact strength	2 Nm / 10 x
cable layer type	Indoors
Halogen-free	According to IEC 60754-2
Resistance to oil	IRM 902 No.2, 100 °C, DIN VDE 0473-811-2-1
Fiber	PCF gradient index, 200/230 µm

Attenuation

660 nm	18 dB/km
850 nm	12 dB/km

Standards and Regulations

Duty cycle testing	Flexible cable conduit capable
Resistance to oil	IRM 902 No.2, 100 °C, DIN VDE 0473-811-2-1
Impact strength	2 Nm / 10 x

FO cable - FL FOC PN-C-HCS-GI-200/230 - 2313410

Technical data

Standards and Regulations

Halogen-free	According to IEC 60754-2
Behavior in fire	1.34 MJ/m (0.37 kWh/m)

Classifications

eCl@ss

eCl@ss 4.0	27061001
eCl@ss 4.1	27061001
eCl@ss 5.0	27061803
eCl@ss 5.1	27061803
eCl@ss 6.0	27061803
eCl@ss 7.0	27061803
eCl@ss 8.0	27061803
eCl@ss 9.0	27061803

ETIM

ETIM 2.0	EC000034
ETIM 3.0	EC000034
ETIM 4.0	EC000034
ETIM 5.0	EC000034

UNSPSC

UNSPSC 6.01	26121607
UNSPSC 7.0901	26121607
UNSPSC 11	26121607
UNSPSC 12.01	26121607
UNSPSC 13.2	26121607

Accessories

Accessories

Assembly tool

Assembly tool - PSM-HCS-KONFTOOL/SC-RJ - 2708876



HCS assembly kit for SC-RJ quick mounting connectors, including stripping blade, stripping pliers, aramide yarn scissors, fiber stripper, microscope, fiber cleaving tool for standard HCS and HCS GI fibers, two SC-RJ connectors for standard HCS fiber, and documentation

FO cable - FL FOC PN-C-HCS-GI-200/230 - 2313410

Accessories

Assembly tool - PSM-HCS-KONFTOOL/B-FOC - 2708465



HCS assembly kit for B-FOC(ST) quick mounting connectors, including stripping blade, stripping pliers, aramide yarn scissors, fiber stripper, microscope, fiber cleaving tool for standard HCS and HCS GI fibers, four B-FOC(ST) connectors for standard HCS fiber, and documentation

Assembly tool - PSM-HCS-CLEAVETOOL/SCRJ - 2313122



Fiber cleaving tool for PCF fibers, pin assignment: SC-RJ or SC duplex for the assembly of SC quick mounting connectors, supplements PSM-PCF-KONFTOOL...

Assembly tool - PSM-HCS-CLEAVETOOL/B-FOC - 2708478



Fiber cleaving tool for PCF fibers, pin assignment: B-FOC (ST) for the assembly of B-FOC quick mounting connectors, supplements PSM-PCF-KONFTOOL...

Stripping tool - PSM-FO-STRIP - 2744199



Stripping pliers for transmitting individual elements of the fiber optic cable. Especially suited for all polymer and PCF cables. Special mechanics and precise blade form avoid damage to the fiber optic fibers. Dimensions: (L x W x H) 160 x 130 x 36 mm.

Connector set

FO connectors - PSM-SET-SCRJ-DUP/2-HCS/PN - 2313546



SC-RJ connector set for standard PROFINET PCF fiber cables with 2.2 mm diameter of the individual elements. Consisting of 2 duplex quick mounting connectors with bend protection for self-assembly.

FO cable - FL FOC PN-C-HCS-GI-200/230 - 2313410

Accessories

FO connectors - PSM-SET-B-FOC/4-HCS/PN - 2313782



B-FOC (ST) connector set for standard PROFINET PCF fiber cables with 2.2 mm diameter of the individual elements. Consisting of 4 quick mounting connectors with bend protection for self-assembly.

FO connectors - PSM-SET-SC-DUPLEX/2-HCS/PN - 2313779



SC duplex connector set for standard PROFINET PCF fiber cables with 2.2 mm diameter of the individual elements. Consisting of 2 duplex quick mounting connectors with bend protection for self-assembly.

Data cable preassembled

FO patch cable - FOC-PN-HCS-GI-1005/IP20/... - 2901554



PROFINET HCS GI installation cable for assembly (IP20 heads only), suitable for drag chains, for indoor installation, gradient index fibers. Individual elements made from highly flexible FRNC material. Halogen-free, ozone and UV resistant with a polyurethane (PUR) outer sheath.

FO patch cable - FOC-PN-HCS-GI-1005/... - 1402189



HCS-GI installation cable for assembly for fixed installation in the inner area, with gradient index fibers for the highest performance requirements, as well as individual elements made of highly flexible FRNC material. The cable is halogen-free, ozone and UV resistant and has a rugged polyurethane (PUR) outer sheath.