


**Part Number: 1840A**

**DBS Cable, Dual RG6, 18 AWG BCCS, Foil + Braid**



**Product Description**

Series 6, 18 AWG solid .040" bare copper-covered steel conductor, gas-injected foam polyethylene insulation, Duobond® II, Al. braid shield (60% coverage), PVC jacket.

**Technical Specifications**

**Product Overview**

Environmental Space:	Indoor (Not Riser or Plenum)
----------------------	------------------------------

**Physical Characteristics (Overall)**

**Conductor**

AWG	Stranding	Material	Nominal Diameter	No. of Coax
18	Solid	BCCS - Bare Copper Covered Steel	0.04 in	2

Conductor, Table Note:	Corrosion Resistance
Conductor Count:	2
Conductor Size:	18 AWG

**Insulation**

Material	Nominal Diameter
Gas-injected FPE - Foam Polyethylene	0.18 in

**Outer Shield Material**

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Aluminum/Polyester/Aluminum	Bonded Duofoil®	100 %
Braid	2	AL - Aluminum		60 %

**Outer Jacket Material**

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.273 x 0.703 in

**Construction and Dimensions**

Static Ground:	BCCS - Bare Copper Covered Steel
Static Ground Diameter:	0.045 in

**Electrical Characteristics**

**Conductor DCR**

Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
28 Ohm/1000ft	9 Ohm/1000ft	9 Ohm/1000ft

**Capacitance**

Nom. Capacitance Conductor to Shield	
16.2 pF/ft	
Shielding:	Multiple or Specialty

**Inductance**

Nominal Inductance
0.097 µH/ft

## Impedance

### Nominal Characteristic Impedance

75 Ohm

## Return Loss (RL)

### Frequency [MHz] | Min. Structural Return Loss (SRL)

950 - 2250 MHz | 15 dB

2250 - 3000 MHz | 10 dB

## High Frequency (Nominal/Typical)

### Frequency [MHz] | Nom. Insertion Loss

5 MHz | 0.5 dB/100ft

55 MHz | 1.4 dB/100ft

211 MHz | 2.6 dB/100ft

500 MHz | 4.1 dB/100ft

750 MHz | 5.1 dB/100ft

862 MHz | 5.5 dB/100ft

1000 MHz | 6 dB/100ft

1450 MHz | 7.8 dB/100ft

1800 MHz | 8.6 dB/100ft

2250 MHz | 9.8 dB/100ft

3000 MHz | 11.3 dB/100ft

## Delay

### Nominal Delay | Nominal Velocity of Propagation (VP) [%]

1.2 ns/ft | 83 %

## High Freq

### Frequency [MHz] | Max. Insertion Loss (Attenuation)

5 MHz | 0.58 dB/100ft

55 MHz | 1.6 dB/100ft

211 MHz | 3.05 dB/100ft

500 MHz | 4.66 dB/100ft

750 MHz | 5.65 dB/100ft

862 MHz | 6.1 dB/100ft

1000 MHz | 6.55 dB/100ft

1450 MHz | 8 dB/100ft

1800 MHz | 8.8 dB/100ft

2250 MHz | 10 dB/100ft

3000 MHz | 11.9 dB/100ft

## Voltage

### Non-UL Voltage Rating

350 V RMS

## Temperature Range

Non-UL Temp Rating: 80°C

Operating Temp Range: -40°C To +80°C

## Mechanical Characteristics

Bulk Cable Weight: 69 lbs/1000ft

Max Recommended Pulling Tension: 195 lbs

Min Bend Radius/Minor Axis: 3 in

## Standards

RG Type: 6/U Type

Series Type: Series 6

RG / Series Type: Series 6

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

### Part Number

#### Variants

Item #	Color	Footnote
1840A 0101000	Black	C
1840A 010500	Black	C

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.