

Fuse DTIII 500V



See below:  
[Approvals and Compliances](#)

---

### Description

- Operation full range cable defensive fuses
- Over-load and short-circuit protection
- Colored characteristic detector in the middle
- Characteristic gG
- According to IEC 269

---

### Technical Data

Rated Current In	32- 63A
Rated Voltage	500 VAC
Breaking Capacity	50kA
Rated Power Operating Frequency fe	50Hz

---

### Basic Design

Insulator	Ceramic
Metal components	Brass

---

### Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

---


### Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

**Time-Current-Curves**

DT II - DT III



Current in Amperes

**All Variants**

Rated current	Color	Packaging unit	Order Number	E-No	
[A]		ST			
32	black	25	0001.2066	800353009	■
35	black	25	0001.2028	800353509	■
40	black	25	0001.2029	800354009	■
50	white	25	0001.2030	800355009	■
63	copper	25	0001.2031	800356009	■

■ Most Popular.

Availability for all products can be searched real-time: <https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>