

## Protect It! 10-Outlet Surge Protector, 8 ft. Cord with Right-Angle Plug, 2395 Joules, Tel/DSL Protection, Black Housing

MODEL NUMBER: TLP1008TEL



Safeguard your PC, printer, scanner, router, modem and other small home electronics against dangerous surges, spikes and line noise. Built-in RJ11 jacks also protect your telephone, fax machine and modem from surges.

### Description

Perfect for your home or office workstation, the TLP1008TEL Protect It!® 10-Outlet Surge Protector features a surge protection rating of 2395 joules to defend your sensitive electronic components against even the strongest surges and spikes.

Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP1008TEL protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G). It also filters out electromagnetic interference (EMI) and radio frequency interference (RFI) that can disrupt your electronics and inflict hardware damage or data loss.

Your devices plug into 10 NEMA 5-15R outlets, four of which are widely spaced to accept bulky transformers without blocking adjacent outlets. Sliding safety covers block accidental contact with unused outlets. RJ11 jacks allow connection of telephone/fax/modem equipment, which is also protected from surges.

An integrated 15A circuit breaker protects all outlets and shuts down connected equipment in case of overload. Diagnostic LEDs confirm your wall outlet is properly grounded and your connected equipment is protected.

The eight-foot AC power cord allows the TLP1008TEL to reach distant outlets, while its right-angle NEMA 5-15P plug allows furniture and equipment to be placed flush against the wall to save space in your workstation. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting

### Highlights

- 10 NEMA 5-15R outlets, including 4 for bulky transformers
- 2395-joule surge protection rating
- Filters out threatening EMI/RFI line noise
- 15A resettable circuit breaker prevents dangerous overloads
- 8 ft. AC power cord with right-angle NEMA 5-15P plug

### Package Includes

- TLP1008TEL Protect It! 10-Outlet Surge Protector, Black Housing
- RJ11 telephone cable, 6 ft.
- Owner's manual

options for the black plastic housing.

## Features

### 2395-Joule Surge Protection for Home or Office Electronics

- Protects your computer, printer, scanner, router, modem and other small home electronics against even the strongest surges and spikes
- Recommended for any desktop, network or home electronics application requiring AC line protection
- Full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Filters out disruptive EMI/RFI line noise that can cause equipment damage or data loss
- Exceeds IEEE 587 Category A and B surge suppression specifications

### 10 Outlets Accept Wide Range of Electronic Devices

- 10 NEMA 5-15R AC outlets accept most computers and peripherals
- 4 widely spaced outlets accommodate bulky transformers without blocking other outlets
- Sliding safety covers block accidental contact with unused outlets

### Telephone/DSL Protection

- RJ11 jacks (1 input/2 output) protect phone/fax/modem equipment from surges and spikes
- Built-in splitter protects 2 devices sharing one line
- 6 ft. RJ11 telephone cable included

### Premium Safety Features

- On/off switch provides one-touch control over connected equipment
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required
- Integrated 15A circuit breaker shuts down outlets in case of power overload
- Diagnostic LEDs confirm grounding and protection status at a glance
- Conforms to current UL 1449 3rd Edition safety standards

### Fits Effortlessly Into Your Workstation

- 8 ft. AC power cord with right-angle NEMA 5-15P plug allows furniture and equipment to be placed flush against the wall
- Keyhole slots on bottom panel provide convenient wall or desk mounting options
- Black plastic housing designed for long life

### Backed by Tripp Lite's Ultimate Lifetime Insurance

- \$150,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

## Specifications



|  |  |
|--|--|
| UPC Code                                     | 037332119063   |
| <b>OUTPUT</b>                                |  |
| Frequency Compatibility                      | 50 / 60 Hz   |
| Output Receptacles                           | (10) 5-15R   |
| Output (Watts)                               | 1800W  |
| Circuit Breaker (amps)                       | 15A  |
| Overload Protection                          | 15A resettable circuit breaker   |
| Transformer Accommodation                    | Supports 4 large transformer plug accessories without covering remaining outlets, accepts up to 8 transformers total |
| Outlet Safety Covers                         | Includes built-in sliding outlet safety covers   |
| Outlet Orientation                           | Two rows of outlets, including 4 widely spaced for transformers  |
| Right-Angle Outlets                          | No   |
| <b>INPUT</b>                                 |  |
| Nominal Input Voltage(s) Supported           | 120V AC  |
| Recommended Electrical Service               | 120V (110-125V)  |
| Input Connection Type                        | NEMA 5-15P   |
| Input Plug Features                          | Space-saving right angle input plug  |
| Input Cord Length (ft.)                      | 8  |
| Input Cord Length (m)                        | 2.44   |
| Input Cord Gauge Type                        | 14 gauge, SJT  |
| Voltage Compatibility (VAC)                  | 120  |
| Maximum Surge Amps                           | 120000   |
| Right-Angle Plug                             | Yes  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |  |
| Switches                                     | Combination AC circuit breaker and two-position on/off power switch  |
| Diagnostic LED Details                       | Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status                            |
| <b>SURGE / NOISE SUPPRESSION</b>             |  |
| AC Suppression Joule Rating                  | 2395   |
| AC Suppression Response Time                 | < 1 ns   |
| Protection Modes                             | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression                                   |
| Clamping Voltage (RMS)                       | 150  |
| UL1449 Let Through Rating                    | 400V - UL Verified   |
| EMI / RFI Filtering                          | Up to 40dB   |



| <b>DATALINE SURGE SUPPRESSION</b>                    |  |
|--|--|
| Telephone/DSL Protection                             | Yes  |
| Telephone/DSL Protection Details                     | 1 line   |
| Cable (Coax) Protection                              | No   |
| Network (Ethernet) Protection                        | No   |
| <b>PHYSICAL</b>                                      |  |
| Shipping Dimensions (hwd / in.)                      | 14.30 x 1.75 x 8.20  |
| Shipping Dimensions (hwd / cm)                       | 36.32 x 4.44 x 20.83   |
| Shipping Weight (lbs.)                               | 2.40   |
| Shipping Weight (kg)                                 | 1.09   |
| Unit Dimensions (hwd / in.)                          | 12 x 5.25 x 2  |
| Unit Dimensions (hwd / cm)                           | 30.48 x 13.33 x 5.08   |
| Unit Weight (lbs.)                                   | 2  |
| Unit Weight (kg)                                     | 0.91   |
| Material of Construction                             | Plastic  |
| Integrated Keyhole Mounting Tabs                     | Keyhole mounting tabs enable wall mounting   |
| Housing Color  | Black  |
| Receptacle Color                                     | Black  |
| Color (AC Line Cord)                                 | Black  |
| Outlets Measurement (Center to Center)               | Between Standard Outlets = 28.4mm; Between Standard and Transformer Outlets = 56.8mm |
| Keyhole Slot Mounting Measurement (Center to Center) | 108mm  |
| <b>CERTIFICATIONS</b>                                |  |
| UL1449 3rd Edition (AC Suppression)                  | UL1449 3rd Edition   |
| UL1363 (Power Tap)                                   | UL1363   |
| UL497A (Communications)                              | UL497A   |
| FCC Part 68 (Communications)                         | FCC Part 68  |
| cUL / CSA (Canada)                                   | cUL  |
| Industry Canada (Communications)                     | Industry Canada  |
| Approvals  | Exceeds IEEE 587 category A&B specifications   |
| <b>WARRANTY</b>                                      |  |
| Product Warranty Period (Worldwide)                  | Lifetime limited warranty  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|   |  |
|---|--|
| Connected Equipment Insurance<br>(U.S., Canada & Puerto Rico) | \$150,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |
|---|--|

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:  
<https://www.tripplite.com/products/product-certification-agencies>