


Extended length is with 500g of force

P1	COLOR
1	WHITE
2	BLACK
3	RED
4	GREEN
5	YELLOW
6	BLUE



Extended Length ("L2")	Typical Retracted Length ("L1")
168.0 Inches - 193.2 Inches	53.5 Inches
4,267.2MM-4,907.28MM	1,358.9MM

**Material:**

- Plug Housing: Polycarbonate, clear
- Plug Terminal: 0.36"[0.14MM] Thick Phosphor Bronze
- Connector: 50µ" of Selective Gold Contact Plating
  - Area, Gold flash over the remainder
  - Over 2.54µm[.000100] thick nickel underplate
- Conductor(X6C): 26AWG (0.12X12) Bare Copper
- Insulation(X6C): PP6331 ID 0.95-1.0
- Jacke: PVC No UL 80 P
- Package: Individual PE Bag

**SBC: A-A**



Scale	1:1						Name	Item No. <b>AT-C-26-6/6/W-14-OE</b>
TOLERANCE					Drawn	11.02.11	Chappell	
X.X	±0.40				Approved			Title NON-UL 26AWG (0.12X12)*6C, O.D.: 2.4*6.8MM, Single Plug, 50µ" of contact plating, WHITE
X.XX	±0.25							
X.XXX	±0.15							Drawing No.
Angle	±3°							<b>rev00</b>
								Replace
								Sheet



Modification      Date      Name